



# COMPACT ONE SIZE ALL PURPOSE KNEEPADS

- FULL PROTECTION
- ONE SIZE FITS ALL
- FOR ALL THE JOBS IN BETWEEN

CERTIFIED FOR PROFESSIONAL FLOOR COVERING INSTALLATION

# **PRO KNEE**<sup>®</sup> **AP16<sup>®</sup> ALL PURPOSE KNEEPADS**







#### ROLLGOODS



# CARPET

LINEOLEU
VINYL
RUBBER
VCT
TPO/PVC
EPDM



# NATURAL STONE MASONRY FLOOR PREPARATION EPOXY

CONCRETE
FLATWORK



## **STRIPWOODS** NATURAL PREFINISHED LAMINATE

DECKING SUBFLOOR

### ALL PARTS REPLACEABLE

 Molded in frame components make replacing parts easy, fast and economical





#### **ON FRAME** PERIMETER RIBBING •Provides maximum flexibility in

extreme kneeling positions •Molded from flexible, tear resistant plastic resin

#### RUBBER BOOT

•Tough 3 ply white polynitrile 3/16" thick non-skid construction Screws to frame •Non-marking material (user's responsibility to keep clean)

## **KNEE POCKET SHAPE & FLAT BOTTOM DESIGN**

·Stabilizes knee joint to reduce joint wear-out & knee burn pain

#### **TUCKED IN LINER**

•3/16" thick •Wicks away moisture •Keeps Cushion Inserts clean •No wrinkle fabrication adds comfort •Offer a snug, stay-it-place fit

# WEIGHT

WEIGHT FOR 1 KNEEPAD LEG FULLY ASSEMBLED:

**Flexible Joint** 5/8" CUSHION AP16—appoximately 1.164 lbs n 0 1" CUSHION AP16 — approximately 1.372 lbs

©@PROKNEE ¶@PROKNEE.TREADMAN **WWW.PR**[] 🐻 @MR.PROKNEE 🛅 @PROKNEE CORP Proknee\* PRO KNEE\* AP16\* SMARTELOCK @ are Registered Trademarks of PROKNEE® CORP. U.S. Patent Numbers 4772071,4876745,7837769,10441007,8561311,11051566. Other Patents Pending. CANADA Patent Number 2617789,285405. EUROPEAN Patent Number 241136

**ADJUSTABLE STRAPS** ·Pre-angled to allow two different strap placement options •1-3/8" W poly woven yarn

CROSSED


PARALLE

# SMARTELOCK PLUS OUICK R



•Ergonomic, larger format buckle is easy on fingers •Automatically locks in your perfect strap length with just a pull to give you a comfortable fit you can work in all day long •1-3/4" W buckles made from plastic resin

# LIVE HINGE





## LIVE HINGE

10.5° Maximum Angle

**URETHANE CUSHION INSERT** 

•2 thickness options - 5/8" and 1" •1 full length piece with wear liner on both sides •Safe & resilient with consistent compression springback to help absorb shock out of day to day wear & tear from kneeling

PATENTED WORLDWIDE